

High-performance tape for carpet skirting

Bullran 45



Secure adhesion of whipped carpet skirtings

Applications:

Special adhesive system for the bonding of textile flooring skirting with a variety of backing structures. Bullran ensures the quick and solvent-free installation for interior areas and meets the TRGS 610.

► Suitable for:

- Fleece backing
- Synthetic double backing (SDR)
- Textile secondary backing (TR)
- Latex foam backing
- Needle punch
- Kugelgarn
- Woven textile flooring

► Suitable for use on:

- Breeze / plaster
- Brickwork
- Metal (untreated)
- Painted surfaces
- Plastics
- Wood
- Concrete
- Ceramics
- Gypsum (primed)
- Wallpaper*
- Levelling compound (primed)

* See Notes for Preparation

Provides the highest possible level of emission safety and contributes towards creating a healthy room climate. Marked with the "Blue Angel" for low-emission floor covering adhesives and other installation materials according to RAL-UZ 113.



ÖKOLINE

for whipped carpet skirting 50 – 60 mm
ON substrates up to 3 mm structure

Ingredients: Acrylic copolymers, wetting and defoaming agents, laid scrim, paper.

Product benefits / Features:

- High-performance adhesive for needle punch, web and fleece backing
- Does not become brittle, providing a strong & permanent bond
- Clean & fast
- Solvent-free / complies with TRGS 610 (technical regulation for dangerous substances)
- "Blue Angel" as per RAL-UZ 113
- EMICODE EC 1 PLUS / very low-emission

Technical specifications:


| | |
|---------------------------|-----------------------------------|
| Packaging: | Carton |
| Width of rolls: | 45 mm |
| Length of rolls: | 25 m |
| Shelf life: | min. 2 years |
| Colour: | transparent with green laid scrim |
| Substrate temperature: | min. 15 °C |
| Open time: | none |
| Working time: | none |
| Set to traffic: | immediately after bonding |
| Sealing / jointing seams: | immediately after bonding |

Note for preparation:

- ▶ The substrate must be permanently dry, hard, load-bearing, flat, free from grease, dust and silicon, in accordance with the respective national standards (EN, DIN, VOB, OE, SIA).
- ▶ Wallpapers must be firmly bonded.
- ▶ Bind dust with a solvent-free primer (e.g. UZIN PE 260).
- ▶ Ensure the floor covering and Bullran 45 are free from contortions before installing. Allow the floor covering (and Bullran 45) to acclimatise sufficiently according to the manufacturers recommendations.

The following is needed:

- ▶ Bullran 45, rubber mallet, carpet knife



Application:



- ▶ Fit Bullran 45 on the back of whipped carpet skirting (by hand or quick and easy with the contact applicator)



- ▶ Pull off the protective paper continuously
- ▶ Position the carpet skirting without twisting



- ▶ Tap in everywhere using a rubber mallet



- ▶ Before removing the protective paper, pre-bend the carpet skirting at the internal / external corners (to relieve tension in skirting)

Contact applicator:



Important notes:

Store in a dry, cool area without exposure to direct sunlight.

- ▶ **Not guaranteed:**
 - Carpet skirting with PVC and PU backing
 - Wooden strips
 - Dirt trap runners
 - PVC soft skirting boards
 - Aluminium skirting
 - Core skirting boards

Protection of the workplace and the environment:

The product does not require any special labour protection measures. For reasons of working hygiene, we recommend avoiding eating, drinking and smoking during processing of this product. Store out of the reach of children.

For more information refer to www.uzin.com or contact +49 (0)731 4097-0

Disposal:

Empty shells and the cardboard packaging can be recycled. Material remnants can be disposed of as household waste.

Warranty:

UZIN grants a 5-year warranty for all properties claimed in the installation instructions.

- Follow the generally acknowledged rules of the trade and of technology for the installation of floor covering of the respective applicable standards (EN, DIN, VOB, OE, SIA)

In all cases, some adhesion tests must be carried out on-site before carrying out the installation.

The warranty becomes void if:

- unusual influences, and in particular those of a chemical or mechanical nature, affect the product.
- used or processed differently than stated in the installation instructions.
- Bullran 45 is used on stairs.
- moisture affects Bullran 45.
- Bullran 45 is used in vehicle manufacturing and operating theatres.
- installation was performed below 15°C (on the wall).
- Bullran 45 is used in areas with increased humidity or thermal exposures (e.g. conservatories).